

# SAFETY DATA SHEET

**Date Printed:** 05/05/2024 **Date Revised:** 01/15/2022

## **SECTION 1. IDENTIFICATION**

Product Identifier: (3N5) 99.95% Calcium Selenide Sputtering Target

Product Code: CA-SE-035-ST

**CAS Number:** 1305-84-6

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551

Fax: +1 310-208-0551

Emergency telephone number:

+1 800-424-9300

## **SECTION 2. HAZARDS IDENTIFICATION**

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 Flame

Water-react. 3 H261 In contact with water releases flammable gas.

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H331 Toxic if inhaled.

GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T; Toxic

R23/25: Toxic by inhalation and if swallowed.

N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R29-33: Contact with water liberates toxic gas. Danger of cumulative effects.

Information concerning particular hazards for human and environment:

N/A

Hazards not otherwise classified

No data available

Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labeled according to the CLP regulation.

Hazard pictograms







GHS02

GHS06

GHS08

Signal word

Danger

Hazard statements

H261 In contact with water releases flammable gas.

H301+H331 Toxic if swallowed or if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P231+P232 Handle under inert gas. Protect from moisture.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

WHMIS classification

B6 - Reactive flammable material

D1A - Very toxic material causing

immediate and serious toxic effects

F - Dangerously reactive material

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

**HEALTH** 

**FIRE** 

**REACTIVITY** 

2

1

2

Health (acute effects) = 2

Flammability = 1

Physical Hazard = 2

Other hazards

Results of PBT and vPvB assessment

PBT:

N/A

vPvB:

N/A

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances

CAS No. / Substance Name:

1305-84-6 Calcium selenide

Identification number(s): EC number: 215-141-5

### **SECTION 4. FIRST AID MEASURES**

Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing has been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

If inhaled:

Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

In case of skin contact:

Immediately wash with soap and water; rinse thoroughly.

Seek immediate medical advice.

In case of eye contact:

Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed:

Do not induce vomiting; immediately call for medical help.

Information for doctor

Most important symptoms and effects, both acute and delayed

No data available

Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5. FIREFIGHTING MEASURES**

Extinguishing media

Suitable extinguishing agents

CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents

Water

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Selenium dioxide (SeO2)

Calcium oxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow material to be released to the environment without official permits.

Do not allow product to enter drains, sewage systems, or other water courses.

Do not allow material to penetrate the ground or soil.

Methods and materials for containment and cleanup:

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Prevention of secondary hazards:

No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7. HANDLING AND STORAGE**

Handling

Precautions for safe handling

Handle under dry protective gas.

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

No data available

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from water/moisture.

Further information about storage conditions:

Store under dry inert gas.

This product is moisture sensitive.

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Protect from humidity and water.

Specific end use(s)

No data available

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Selenium and selenium compounds (as Se)

mg/m3

ACGIH TLV 0.2

Austria MAK 0.1

Belgium TWA 0.2 Denmark TWA 0.1

Finland TWA 0.1; 0.3-STEL

Germany MAK 0.1

Hungary 0.1-STEL

Ireland TLV 0.1

Japan OEL 0.1

Korea TLV 0.2

Netherlands MAC-TGG 0.1

Poland TWA 0.1; 0.3-STEL

Sweden NGV 0.1

Switzerland MAK-W 0.1

United Kingdom TWA 0.1

USA PEL 0.2

Additional information:

No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Impervious gloves

Inspect gloves prior to use.

Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.

Penetration time of glove material (in minutes)

No data available

Eye protection:

Safety glasses

Body protection:

Protective work clothing.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance:

Form: Powder or solid

Color: White

Odor:Characteristic

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: No data available Boiling point/Boiling range: No data available Sublimation temperature / start: No data available

Flammability (solid, gas)

No data available.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion: Product does not present an explosion hazard.

**Explosion limits:** 

Lower: No data available Upper: No data available Vapor pressure: N/A

Density at 20 °C (68 °F): 3.57 g/cm<sup>3</sup> (29.792 lbs/gal)

Relative density No data available. Vapor density

N/A

Evaporation rate

N/A

Solubility in Water (H<sub>2</sub>O): Contact with water releases toxic gases

Partition coefficient (n-octanol/water): No data available.

Viscosity: Dynamic: N/A Kinematic: N/A Other information No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

Contact with water releases toxic gases

Contact with acids releases toxic gases

Conditions to avoid

No data available

Incompatible materials:

Oxidizing agents

Water/moisture

Hazardous decomposition products:

Selenium dioxide (SeO2)

Calcium oxide

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on toxicological effects

Acute toxicity:

Toxic if inhaled.

Toxic if swallowed.

LD/LC50 values that are relevant for classification:

No data

Skin irritation or corrosion:

May cause irritation

Eye irritation or corrosion:

May cause irritation

Sensitization:

No sensitizing effects known.

Germ cell mutagenicity:

No effects known.

Carcinogenicity:

No classification data on carcinogenic properties of this material is available from the EPA, IARC,

NTP, OSHA or ACGIH.

Reproductive toxicity:

No effects known.

Specific target organ system toxicity - repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Specific target organ system toxicity - single exposure:

No effects known.

Aspiration hazard:

No effects known.

Subacute to chronic toxicity:

Selenium may cause amyotropic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatigue, loss of fingernails and hair, pulmonary edema, anemia and weight loss.

The toxicity of calcium compounds is generally due to the anion.

Subacute to chronic toxicity:

No effects known.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

## **SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity** 

Aquatic toxicity:

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Ecotoxical effects:

Remark:

Very toxic for aquatic organisms

Additional ecological information:

Do not allow material to be released to the environment without official permits.

Do not allow product to reach groundwater, water courses, or sewage systems, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

May cause long lasting harmful effects to aquatic life.

Avoid transfer into the environment.

Very toxic for aquatic organisms

Results of PBT and vPvB assessment

PBT:

N/A vPvB: N/A

Other adverse effects No data available

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste treatment methods

Recommendation

Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

## **SECTION 14. TRANSPORT INFORMATION**

**UN-Number** 

DOT, IMDG, IATA

UN3134

UN proper shipping name

DOT

Water-reactive solid, toxic, n.o.s. (Calcium selenide)

IMDG, IATA

WATER-REACTIVE SOLID, TOXIC, N.O.S. (Calcium selenide)

Transport hazard class(es)

DOT

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3 + 6.1

Class

4.3 (WT2) Substances which, in contact with water, emit flammable gases

Label

4.3 + 6.1

IMDG, IATA

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3 + 6.1

Packing group

DOT, IMDG, IATA

Ш

Environmental hazards: Environmentally hazardous substance, solid

Special precautions for user

Warning: Substances which, in contact with water, emit flammable gases Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N/A

Transport/Additional information: DOT

Marine Pollutant (DOT): No UN "Model Regulation":

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL).

SARA Section 313 (specific toxic chemical listings)

1305-84-6 Calcium selenide

California Proposition 65

Prop 65 - Chemicals known to cause cancer

Substance is not listed.

Prop 65 - Developmental toxicity

Substance is not listed.

Prop 65 - Developmental toxicity, female

Substance is not listed.

Prop 65 - Developmental toxicity, male

Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product contains selenium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986

and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed. Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use)

Substance is not listed.

REACH - Pre-registered substances

Substance is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.