

SAFETY DATA SHEET

Date Printed: 05/24/2022

Date Revised: 05/15/2015

SECTION 1. IDENTIFICATION

Product Name: Barium Tungsten Isopropoxide

Product Number: All applicable American Elements product codes, e.g. BAW-IP-01-SOL

CAS #: 333971-25-8

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351

Emergency telephone number:

+1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H336 May cause drowsiness or dizziness.

Hazards not otherwise classified No data available

GHS label elements, including precautionary statements



Hazard pictograms

GHS02 GHS07

Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P302+P352 IF ON SKIN: Wash with plenty of water

WHMIS classification

B2 - Flammable liquid

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH

FIRE

REACTIVITY

1

3

1

Health (acute effects) = 1

Flammability = 3

Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: N/A

vPvB: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

CAS No. / Substance Name:

333971-25-8 Barium tungsten isopropoxide, 10% inisopropanol

SECTION 4. FIRST AID MEASURES

Description of first aid measures

If inhaled:

Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

In case of skin contact:

Immediately wash with soap and water; rinse thoroughly.

Seek immediate medical advice.

In case of eye contact:

Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed:

Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed:

No data available

Indication of any immediate medical attention and special treatment needed:

No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents CO₂, sand, extinguishing powder. Do not use water.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Carbon monoxide and carbon dioxide

Barium oxide

Metal oxide fume

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions: Do not allow material to be released to the environment without official permits.

Methods and materials for containment and cleanup:

Keep away from ignition sources.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling

Handle under dry protective gas.

Handle under protective gas.

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from water/moisture.

Further information about storage conditions:

Store under dry inert gas.

This product is moisture sensitive.

Keep container tightly sealed.
Store in cool, dry conditions in well-sealed containers.
Protect from humidity and water.
Specific end use(s) No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Barium, and soluble compounds, as Ba

mg/m³

ACGIH TLV 0.5; Not classified as a human carcinogen

Austria MAK 0.5

Belgium TWA 0.5

Denmark TWA 0.5

Finland TWA 0.5

Germany MAK 0.5 (total dust)

Hungary 0.5-STEL

Ireland TWA 0.5

Korea TLV 0.5

Netherlands MAC-TGG 0.5

Norway TWA 0.5

Poland TWA 0.5; 1.5-STEL

Sweden TWA 0.5

Switzerland MAK-W 0.5

United Kingdom LTEL 0.5

USA PEL 0.5

Tungsten and compounds (as W)

mg/m³

ACGIH TLV 5; 10-STEL (metal)

1; 3-STEL (soluble compounds)

5; 10-STEL (insoluble compounds)

Belgium TWA 1 (soluble compounds)

5; 10-STEL (insoluble compounds)

Finland TWA 5 (metal)

1 (soluble compounds)

5 (insoluble compounds)

Netherlands MAC-TGG 5 (metal)

1 (soluble compounds)

5 (insoluble compounds)

Poland TWA 5 (metal)

1 (soluble compounds)

5 (insoluble compounds)

Sweden NGV 5 (metal)

1 (soluble compounds)

5 (insoluble compounds)

United Kingdom TWA 5; 10-STEL (metal)

1; 3-STEL (soluble compounds)

5; 10-STEL (insoluble compounds)

MSHA TWA 1 (soluble compounds)

5 (insoluble compounds)
Isopropyl alcohol (2-Propanol)
ppm
ACGIH TLV 400; 500-STEL
Austria MAK 400
Belgium TWA 400; 500-STEL
Denmark TWA 200
France VLE 400
Germany MAK 400
Ireland TWA 400; 500-STEL (skin)
Japan TWA 400-STEL
Korea TWA 400; 500-STEL
Netherlands MAC-TGG 400 (skin)
Norway TWA 100
Poland TWA 900; 1200-STEL
Russia TWA 400-STEL
Sweden NGV 150; 250-STEL
Switzerland MAK-W 400
United Kingdom TWA 400; 500-STEL
OSHA PEL 400

Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Protection of hands:

Impervious gloves

Inspect gloves prior to use.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Safety glasses

Body protection: Protective work clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Liquid

Color: Yellow

Odor: Alcohol-like

Odor threshold: No data available.

pH: No data available.

Melting point/Melting range: No data available

Boiling point/Boiling range: No data available

Sublimation temperature / start: No data available

Flash point: 12 °C (54 °F) (i-PrOH)

Flammability (solid, gas) No data available.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Explosion limits:

Lower: No data available

Upper: No data available

Vapor pressure: No data available

Density: No data available

Relative density No data available.

Vapor density No data available.

Evaporation rate No data available.

Solubility in / Miscibility with

Water: Hydrolyzes

Partition coefficient (n-octanol/water): No data available.

Viscosity:

Dynamic: No data available.

Kinematic: No data available.

Other information No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No data available

Incompatible materials:

Oxidizing agents

Water/moisture

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Metal oxide fume

Barium oxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

Harmful if inhaled.

Harmful if swallowed.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: May cause irritation

Eye irritation or corrosion: May cause irritation

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

Carcinogenicity:

IARC-3: Not classifiable as to carcinogenicity to humans.

ACGIH A4: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure:

May cause drowsiness or dizziness.

May cause respiratory irritation.

Aspiration hazard: No effects known.

Subacute to chronic toxicity:

Barium compounds may cause severe gastroenteritis, including abdominal pain, vomiting and diarrhea, tremors, faintness, paralysis of the arms and legs, and slow or irregular heartbeat. Severe cases may produce collapse and death due to respiratory failure.

Soluble barium compounds are more likely to cause these effects than insoluble compounds. Inhalation of fumes may cause sore throat, coughing, labored breathing, and irritation of the respiratory tract as well as the above symptoms.

Tungsten compounds may be irritating to the eyes and respiratory tract. Chronic exposure may result in permanent lung damage.

2-Propanol (isopropyl alcohol) may act as a local irritant and in high concentrations as a narcotic with symptoms such as headache, nausea, dizziness, vomiting, mental depression, anesthesia, and coma. Similar symptoms may be caused by ingestion. It can cause corneal burns on contact with the eyes and has caused teratogenic, mutagenic and reproductive effects in laboratory animals.

Subacute to chronic toxicity: No effects known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No data available

Persistence and degradability No data available

Bioaccumulative potential No data available

Mobility in soil No data available

Additional ecological information:

Do not allow material to be released to the environment without official permits.

Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: N/A

vPvB: N/A

Other adverse effects No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number
DOT, IMDG, IATA UN1219
UN proper shipping name
DOT Isopropanol (Isopropyl alcohol)
IMDG, IATA ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es)
DOT
Class 3 Flammable liquids.
Label 3
Class 3 (F1) Flammable liquids
Label 3
IMDG, IATA
Class 3 Flammable liquids.
Label 3
Packing group
DOT, IMDG, IATA II
Environmental hazards: N/A
Special precautions for user Warning: Flammable liquids
EMS Number: F-E,S-D
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N/A
Transport/Additional information:
DOT
Marine Pollutant (DOT): No
UN "Model Regulation": UN1219, Isopropanol (Isopropyl alcohol), 3, II

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements, including precautionary statements
Hazard pictograms
GHS02 GHS07
Signal word Danger
Hazard statements
H225 Highly flammable liquid and vapor.
H302+H332 Harmful if swallowed or if inhaled.
H336 May cause drowsiness or dizziness.
Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P302+P352 IF ON SKIN: Wash with plenty of water
National regulations
This product is not listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory. Use of this product is restricted to research and development only. This product must be used by or directly under the supervision of a technically qualified individual as defined by TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.
SARA Section 313 (specific toxic chemical listings)
333971-25-8 Barium tungsten isopropoxide, 10% isopropanol
California Proposition 65
Prop 65 - Chemicals known to cause cancer Substance is not listed.
Prop 65 - Developmental toxicity Substance is not listed.
Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product contains barium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.

Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.