

SAFETY DATA SHEET

Date Accessed: 04/19/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Name: Calcium Selenide Sputtering Target

Product Number: All applicable American Elements product codes, e.g. CA-SE-02-ST , CA-SE-025-ST , CA-SE-03-ST , CA-SE-035-ST , CA-SE-04-ST , CA-SE-05-ST

CAS #: 1305-84-6

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351

Emergency telephone number:

+1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS02 Flame

Water-react. 3 H261 In contact with water releases flammable gas.

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H331 Toxic if inhaled.

GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T; Toxic

R23/25: Toxic by inhalation and if swallowed.

N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R29-33: Contact with water liberates toxic gas. Danger of cumulative effects.

Information concerning particular hazards for human and environment:

N/A

Hazards not otherwise classified

No data available

Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS02

GHS06

GHS08

Signal word

Danger

Hazard statements

H261 In contact with water releases flammable gas.

H301+H331 Toxic if swallowed or if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P231+P232 Handle under inert gas. Protect from moisture.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/
national/international regulations.

WHMIS classification

B6 - Reactive flammable material

D1A - Very toxic material causing
immediate and serious toxic effects

F - Dangerously reactive material

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH

FIRE

REACTIVITY

2

1

2

Health (acute effects) = 2

Flammability = 1

Physical Hazard = 2

Other hazards

Results of PBT and vPvB assessment

PBT:

N/A

vPvB:

N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

CAS No. / Substance Name:

1305-84-6 Calcium selenide
Identification number(s):
EC number:
215-141-5

SECTION 4. FIRST AID MEASURES

Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing has been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

If inhaled:

Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

In case of skin contact:

Immediately wash with soap and water; rinse thoroughly.

Seek immediate medical advice.

In case of eye contact:

Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed:

Do not induce vomiting; immediately call for medical help.

Information for doctor

Most important symptoms and effects, both acute and delayed

No data available

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents

Water

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Selenium dioxide (SeO₂)

Calcium oxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow material to be released to the environment without official permits.

Do not allow product to enter drains, sewage systems, or other water courses.

Do not allow material to penetrate the ground or soil.

Methods and materials for containment and cleanup:

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Prevention of secondary hazards:

No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling

Handle under dry protective gas.

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

No data available

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from water/moisture.

Further information about storage conditions:

Store under dry inert gas.

This product is moisture sensitive.

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Protect from humidity and water.

Specific end use(s)

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Selenium and selenium compounds (as Se)

mg/m³

ACGIH TLV 0.2

Austria MAK 0.1
Belgium TWA 0.2
Denmark TWA 0.1
Finland TWA 0.1; 0.3-STEL
Germany MAK 0.1
Hungary 0.1-STEL
Ireland TLV 0.1
Japan OEL 0.1
Korea TLV 0.2
Netherlands MAC-TGG 0.1
Poland TWA 0.1; 0.3-STEL
Sweden NGV 0.1
Switzerland MAK-W 0.1
United Kingdom TWA 0.1
USA PEL 0.2

Additional information:

No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Impervious gloves

Inspect gloves prior to use.

Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.

Penetration time of glove material (in minutes)

No data available

Eye protection:

Safety glasses

Body protection:

Protective work clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Powder or solid

Color: White

Odor: Characteristic

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: No data available

Boiling point/Boiling range: No data available

Sublimation temperature / start: No data available

Flammability (solid, gas)

No data available.

Ignition temperature: No data available
Decomposition temperature: No data available
Autoignition: No data available.
Danger of explosion: Product does not present an explosion hazard.
Explosion limits:
Lower: No data available
Upper: No data available
Vapor pressure: N/A
Density at 20 °C (68 °F): 3.57 g/cm³ (29.792 lbs/gal)
Relative density
No data available.
Vapor density
N/A
Evaporation rate
N/A
Solubility in Water (H₂O): Contact with water releases toxic gases
Partition coefficient (n-octanol/water): No data available.
Viscosity:
Dynamic: N/A
Kinematic: N/A
Other information
No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity
No data available
Chemical stability
Stable under recommended storage conditions.
Thermal decomposition / conditions to be avoided:
Decomposition will not occur if used and stored according to specifications.
Possibility of hazardous reactions
Contact with water releases toxic gases
Contact with acids releases toxic gases
Conditions to avoid
No data available
Incompatible materials:
Oxidizing agents
Water/moisture
Hazardous decomposition products:
Selenium dioxide (SeO₂)
Calcium oxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Acute toxicity:
Toxic if inhaled.
Toxic if swallowed.
LD/LC50 values that are relevant for classification:
No data

Skin irritation or corrosion:
May cause irritation
Eye irritation or corrosion:
May cause irritation
Sensitization:
No sensitizing effects known.
Germ cell mutagenicity:
No effects known.
Carcinogenicity:
No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.
Reproductive toxicity:
No effects known.
Specific target organ system toxicity - repeated exposure:
May cause damage to organs through prolonged or repeated exposure.
Specific target organ system toxicity - single exposure:
No effects known.
Aspiration hazard:
No effects known.
Subacute to chronic toxicity:
Selenium may cause amyotrophic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatigue, loss of fingernails and hair, pulmonary edema, anemia and weight loss.
The toxicity of calcium compounds is generally due to the anion.
Subacute to chronic toxicity:
No effects known.
Additional toxicological information:
To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity
Aquatic toxicity:
No data available
Persistence and degradability
No data available
Bioaccumulative potential
No data available
Mobility in soil
No data available
Ecotoxicological effects:
Remark:
Very toxic for aquatic organisms
Additional ecological information:
Do not allow material to be released to the environment without official permits.
Do not allow product to reach groundwater, water courses, or sewage systems, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
May cause long lasting harmful effects to aquatic life.
Avoid transfer into the environment.
Very toxic for aquatic organisms
Results of PBT and vPvB assessment

PBT:
N/A
vPvB:
N/A
Other adverse effects
No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods
Recommendation
Consult official regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation:
Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number
DOT, IMDG, IATA
UN3134
UN proper shipping name
DOT
Water-reactive solid, toxic, n.o.s. (Calcium selenide)
IMDG, IATA
WATER-REACTIVE SOLID, TOXIC, N.O.S. (Calcium selenide)
Transport hazard class(es)
DOT
Class
4.3 Substances which, in contact with water, emit flammable gases.
Label
4.3+6.1
Class
4.3 (WT2) Substances which, in contact with water, emit flammable gases
Label
4.3+6.1
IMDG, IATA
Class
4.3 Substances which, in contact with water, emit flammable gases.
Label
4.3+6.1
Packing group
DOT, IMDG, IATA
III
Environmental hazards: Environmentally hazardous substance, solid
Special precautions for user
Warning: Substances which, in contact with water, emit flammable gases
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
N/A
Transport/Additional information: DOT
Marine Pollutant (DOT): No

UN "Model Regulation":

UN3134, Water-reactive solid, toxic, n.o.s. (Calcium selenide), 4.3 (6.1), III

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture
National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL).

SARA Section 313 (specific toxic chemical listings)

1305-84-6 Calcium selenide

California Proposition 65

Prop 65 - Chemicals known to cause cancer

Substance is not listed.

Prop 65 - Developmental toxicity

Substance is not listed.

Prop 65 - Developmental toxicity, female

Substance is not listed.

Prop 65 - Developmental toxicity, male

Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product contains selenium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.
Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.
Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use)

Substance is not listed.

REACH - Pre-registered substances

Substance is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.
