




Disulfur Dichloride		Pricing >
Linear Formula	S ₂ Cl ₂	
Pubchem CID	24807	
MDL Number	MFCD00011446	
EC No.	233-036-2	
IUPAC Name	chlorosulfanyl thiohypochlorite	
SMILES	S(SCl)Cl	
Inchl Identifier	InChI=1S/Cl2S2/c1-3-4-2	
Inchl Key	PXJJSXABGXMUSU-UHFFFAOYSA-N	
Signal Word	Danger	
Hazard Statements	H301-H332-H314-H335-H400-EUH014-EUH029	
Hazard Codes	T, C, N	
Precautionary Statements	P273-P280-P301 + P330 + P331-P304 + P340-P305 + P351 + P338-P308 + P310	
Flash Point	>130 °C	
Risk Codes	N/A	
Safety Statements	N/A	
RTECS Number	N/A	
Transport Information	UN 1828 , 8, I	
WGK Germany	3	
GHS Pictograms	GHS05 Corrosive  GHS09 Environment  GHS06 Skull and Crossbones 	

[Create Printable PDF](#)

SAFETY DATA SHEET

Date Accessed: 04/18/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifiers: All applicable American Elements product codes for CAS #10025-67-9

Relevant identified uses of the substance:
Scientific research and development

Supplier details:
American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351

Emergency telephone number:
Domestic, North America +1 800-424-9300
International +1 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture
GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301
Acute toxicity, Inhalation (Category 3), H331
Skin corrosion (Category 1A), H314
Serious eye damage (Category 1), H318
Acute aquatic toxicity (Category 1), H400

2.2 GHS Label elements, including precautionary statements



Pictogram

Signal word Danger

Hazard statement(s)

H301 + H331 Toxic if swallowed or if inhaled

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

Precautionary statement(s)

P261 Avoid breathing dust/ fume/ gas/ mist/ Vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P363 Wash contaminated clothing before reuse.
P391 Collect spillage.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.
2.3 Hazards not otherwise classified (HNOC) or not covered by GHS
Reacts violently with water., Contact with water liberates toxic gas.
Lachrymator.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms : Sulfur chloride

Formula : Cl₂S₂

Molecular weight : 135.04 g/mol

CAS-No. : 10025-67-9

EC-No. : 233-036-2

Index-No. : 016-012-00-4

Hazardous components

Component Classification Concentration

Sulfur chloride

Acute Tox. 3; Skin Corr. 1A;

Eye Dam. 1; Aquatic Acute 1;

H301 + H331, H314, H318,

H400
<= 100 %

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.

Take victim

immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Dry powder

5.2 Special hazards arising from the substance or mixture

Sulphur oxides, Hydrogen chloride gas

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing Vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Do not flush with water. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of Vapor or mist.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully

resealed and kept upright to prevent leakage.

Never allow product to get in contact with water during storage.

Store under inert gas.

Storage class (TRGS 510): Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component CAS-No. Value Control
parameters
Basis
Sulfur chloride 10025-67-9 TWA 1.000000 ppm
6.000000
mg/m3
USA. Occupational Exposure Limits
(OSHA) - Table Z-1 Limits for Air
Contaminants
Remarks The value in mg/m3 is approximate.
C 1.000000 ppm
USA. ACGIH Threshold Limit Values
(TLV)
Upper Respiratory Tract irritation
Eye irritation
Skin irritation
C 1 ppm
USA. ACGIH Threshold Limit Values
(TLV)
Upper Respiratory Tract irritation
Eye irritation
Skin irritation
C 1.000000 ppm
6.000000
mg/m3
USA. NIOSH Recommended
Exposure Limits
C 1 ppm
6 mg/m3
USA. NIOSH Recommended
Exposure Limits
TWA 1 ppm
6 mg/m3
USA. Occupational Exposure Limits
(OSHA) - Table Z-1 Limits for Air
Contaminants
The value in mg/m3 is approximate.
8.2 Exposure controls
Appropriate engineering controls
Avoid contact with skin, eyes and clothing. Wash
hands before breaks and immediately after handling
the product.
Personal protective equipment
Eye/face protection
Tightly fitting safety goggles. Faceshield (8-inch
minimum). Use equipment for eye protection tested
and
approved under appropriate government standards
such as NIOSH (US) or EN 166(EU).
Skin protection
Handle with gloves. Gloves must be inspected prior to
use. Use proper glove removal technique (without
touching glove's outer surface) to avoid skin contact
with this product. Dispose of contaminated gloves
after

use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Fluorinated rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an

industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It

should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose

combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- a) Appearance Form: clear, liquid
 - b) Odor No data available
 - c) Odor Threshold No data available
 - d) pH No data available
 - e) Melting point/freezing point
Melting point/range: -80 °C (-112 °F) - lit.
 - f) Initial boiling point and boiling range
138 °C (280 °F) - lit.
 - g) Flash point > 130 °C (> 266 °F) - closed cup
 - h) Evaporation rate No data available
 - i) Flammability (solid, gas) No data available
 - j) Upper/lower flammability or explosive limits
No data available
 - k) Vapor pressure 9.1 hPa (6.8 mmHg) at 20 °C (68 °F)
59 hPa (44 mmHg) at 55 °C (131 °F)
 - l) Vapor density 4.66 - (Air = 1.0)
 - m) Relative density 1.688 g/cm³ at 25 °C (77 °F)
 - n) Water solubility No data available
 - o) Partition coefficient: noctanol/water
No data available
 - p) Auto-ignition temperature
390 °C (734 °F)
 - q) Decomposition temperature
No data available
 - r) Viscosity No data available
 - s) Explosive properties No data available
 - t) Oxidizing properties No data available
- ### 9.2 Other safety information
- Relative Vapor density 4.66 - (Air = 1.0)
-

SECTION 10. STABILITY AND REACTIVITY

- ### 10.1 Reactivity
- No data available
- ### 10.2 Chemical stability
- Stable under recommended storage conditions.
- ### 10.3 Possibility of hazardous reactions
- Reacts violently with water.
- ### 10.4 Conditions to avoid
- Exposure to moisture

10.5 Incompatible materials

Strong oxidizing agents
Reacts violently with water.,
Alcohols, Metals, Peroxides, Amines

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 132 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 2.5
mg/l

(OECD Test Guideline 403)

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: WS4300000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.,
spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary
edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

UN number: 3390 Class: 6.1 (8) Packing group: I

Proper shipping name: Toxic by inhalation liquid, corrosive, n.o.s. (Sulfur chloride)

Reportable Quantity (RQ):
Marine pollutant:yes
Poison Inhalation Hazard: Hazard zone B
IMDG
UN number: 3390 Class: 6.1 (8) Packing group: I
EMS-No: F-A, S-B
Proper shipping name: TOXIC BY INHALATION
LIQUID, CORROSIVE, N.O.S. (Sulfur chloride)
Marine pollutant:yes
IATA
UN number: 3390 Class: 6.1 (8)
Proper shipping name: Toxic by inhalation liquid,
corrosive, n.o.s. (Sulfur chloride)
IATA Passenger: Not permitted for transport
IATA Cargo: Not permitted for transport

SECTION 15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De

Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard

Massachusetts Right To Know Components

Sulfur chloride 10025-67-9 1993-04-24

Pennsylvania Right To Know Components

Sulfur chloride

CAS-No.

10025-67-9

Revision Date

1993-04-24

New Jersey Right To Know Components

Sulfur chloride

CAS-No.

10025-67-9

Revision Date

1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.
