

Gold Beryllium Pellets		Pricing >
Gold Beryllium Pieces		Pricing >
Gold Beryllium Rod		Pricing >
Gold Beryllium Slugs		Pricing >
Linear Formula		Au-Be
MDL Number		N/A
EC No.		N/A
Signal Word	Danger	
Hazard Statements	H350-H373-H332-H317	
Hazard Codes	T, Xn, Xi	
Risk Codes	49-23-43-48/20	
Safety Statements	53-4-9-20-24-37-45-60	
RTECS Number	N/A	
Transport Information	N/A	
WGK Germany	N/A	

Create Printable PDF

### **SAFETY DATA SHEET**

**Date Accessed:** 04/16/2024 **Date Revised:** 01/15/2022

### **SECTION 1. IDENTIFICATION**

**Product Identifiers:** All applicable American Elements product codes for CAS #12044-69-8

### Relevant identified uses of the substance:

Scientific research and development

Supplier details: American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551

Fax: +1 310-208-0351

Emergency telephone number:

#### SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)

GHS08 Health hazard

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to the lung and the blood through prolonged or repeated exposure.

Route of exposure: Inhalative.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Hazards not otherwise classified No data available GHS label elements, including precautionary statements

Hazard pictograms





GHS07 GHS08

Signal word Danger

Hazard-determining components of labeling:

Beryllium

Hazard statements

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H373 May cause damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe

dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing

dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)
HEALTH
FIRE
REACTIVITY
1

Health (acute effects) = 1
Flammability = 0
Physical Hazard = 0
Other hazards
Results of PBT and vPvB assessment

PBT: N/A vPvB: N/A

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Dangerous components:

7440-41-7 Beryllium

Acute Tox. 3, H301; Acute Tox. 2, H330; Carc. 1B, H350; STOT RE 1, H372; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 1.0%

Additional information None known. Non-Hazardous Ingredients 7440-57-5 Gold 99.0%

#### **SECTION 4. FIRST AID MEASURES**

4 First-aid measures

Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing has been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

No special measures required.

If inhaled: Seek medical treatment in case of complaints.

In case of skin contact: Generally the product does not irritate the skin.

In case of eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

If swallowed:

If symptoms persist consult doctor.

Information for doctor

Most important symptoms and effects, both acute and delayed:

No data available

Indication of any immediate medical attention and special treatment needed:

No data available

#### **SECTION 5. FIREFIGHTING MEASURES**

Extinguishing media

Suitable extinguishing agents Product is not flammable. Use fire-fighting measures that suit the surrounding fire.

Special hazards arising from the substance or mixture If this product is involved in a fire, the following can be released:

Beryllium oxide

Advice for firefighters

Protective equipment: No special measures required.

# SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions: Do not allow material to be released to the environment without official permits.

Methods and materials for containment and cleanup: Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards: No special measures required.

Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7. HANDLING AND STORAGE**

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

The product is not flammable

No special measures required.

Conditions for safe storage, including any

incompatibilities

Requirements to be met by storerooms and

receptacles: No special requirements.

Information about storage in one common storage

facility:

Store away from oxidizing agents.

Store away from mineral acids

Store away from ammonia

Store away from acetylene.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Specific end use(s) No data available

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical

systems: No further data; see section 7.

Control parameters

Components with limit values that require monitoring

at the workplace:

7440-41-7 Beryllium (1.0%)

PEL (USA) Long-term value: 0.002 mg/m<sup>3</sup>

Ceiling limit value: 0.005; 0.025\* mg/m<sup>3</sup>

as Be; \*30 min peak per 8-hr shift

REL (USA) Ceiling limit value: 0.0005 mg/m<sup>3</sup>

as Be; See Pocket Guide App. A

TLV (USA) Long-term value: 0.00005\* mg/m<sup>3</sup> as Be;\*inhalable; (SEN)NIC-DSEN;RSEN;Skin

EL (Canada) Long-term value: 0.002 mg/m<sup>3</sup>

as Be; ACIGH A1, IARC 1

EV (Canada) Short-term value: 0.01 mg/m<sup>3</sup>

Long-term value: 0.002 mg/m<sup>3</sup>

as Be

Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for

handling chemicals.

Store protective clothing separately.

Maintain an ergonomically appropriate working

environment.

Breathing equipment:

Not required.

Use self-contained respiratory protective device in

emergency situations.

Protection of hands: Not required.

Penetration time of glove material (in minutes) No

data available

Eye protection: Safety glasses

Body protection: Protective work clothing.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Solid in various forms

Color: Gold colored Odor: Odorless

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: 1064 °C (1947 °F) (Au) Boiling point/Boiling range: No data available Sublimation temperature / start: No data available Flammability (solid, gas) No data available.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: Product is not selfigniting. Danger of explosion: No data available.

**Explosion limits:** 

Lower: No data available Upper: No data available Vapor pressure: N/A

Density at 20 °C (68 °F): 19.32 g/cm<sup>3</sup> (161.225

lbs/gal) (Au)

Relative density No data available.

Vapor density N/A Evaporation rate N/A

Solubility in / Miscibility with

Water: Insoluble

Partition coefficient (n-octanol/water): No data

available.
Viscosity:
Dynamic: N/A
Kinematic: N/A
Solvent content:

Organic solvents: 0.0 % Solids content: 100.0 %

Other information No data available

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity No data available

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions Reacts with strong oxidizing agents

Conditions to avoid No data available

Incompatible materials:

Mineral acids

Oxidizing agents

Ammonia

Acetylene

Hazardous decomposition products: Beryllium oxide

# SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

Fatal if inhaled.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for components in this product.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: May cause irritation Eye irritation or corrosion: May cause irritation Sensitization: May cause an allergic skin reaction. Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for components in this product.

Carcinogenicity:

May cause cancer.

EPA-L: Likely to produce cancer in humans.

IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.

ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.

EPA-B1: Probable human carcinogen, limited evidence of carcinogenicity from epidemiologic studies.

NTP-K: Known to be carcinogenic: sufficient evidence from human studies.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains tumorigenic and/or carcinogenic and/or neoplastic data for components in this product. Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure:

May cause damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Specific target organ system toxicity - single

exposure: No effects known.

Aspiration hazard: No effects known.

Subacute to chronic toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic Irritant

Carcinogenic if inhaled.

### **SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity** 

Aquatic toxicity: No data available

Persistence and degradability No data available Bioaccumulative potential No data available

Mobility in soil No data available Additional ecological information:

Do not allow material to be released to the

environment without official permits. Avoid transfer into the environment. Results of PBT and vPvB assessment

PBT: N/A vPvB: N/A

Other adverse effects No data available

# SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

### **SECTION 14. TRANSPORT INFORMATION**

UN-Number DOT, ADN, IMDG, IATA N/A UN proper shipping name DOT, ADN, IMDG, IATA N/A Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA Class N/A Packing group

DOT, IMDG, IATA N/A

Environmental hazards:

Marine pollutant (IMDG): No

Special precautions for user N/A

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code N/A

Transport/Additional information:

DOT

Marine Pollutant (DOT): No UN "Model Regulation": -

# SECTION 15. REGULATORY INFORMATION

Safety, health and environmental

regulations/legislation specific for the substance or mixture

GHS label elements, including precautionary

statements

Hazard pictograms

**GHS07 GHS08** 

Signal word Danger

Hazard-determining components of labeling:

Beryllium

Hazard statements

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H373 May cause damage to the lung and the blood through prolonged or repeated exposure. Route of

exposure: Inhalative.

Precautionary statements

P260 Do not breathe

dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing

dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S.

**Environmental Protection Agency Toxic Substances** 

Control Act Chemical substance Inventory.

All components of this product are listed on the

Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings)

7440-41-7 Beryllium 1.0%

California Proposition 65

Prop 65 - Chemicals known to cause cancer

7440-41-7 Beryllium 1.0%

Prop 65 - Developmental toxicity

None of the ingredients are listed.

Prop 65 - Developmental toxicity, female

None of the ingredients are listed.

Prop 65 - Developmental toxicity, male

None of the ingredients are listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.

None of the ingredients are listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

None of the ingredients is listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use)

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.