

| <u>Lithium Aluminum Hydride</u>          |                              | Pricing > |
|--|------------------------------|-----------|
| <u>Lithium Aluminum Hydride Solution</u> |                              | Pricing > |
| Linear Formula                           | LiAIH <sub>4</sub>           |           |
| Pubchem CID                              | 21226445                     |           |
| MDL Number                               | MFCD00011075                 |           |
| EC No.                                   | 240-877-9                    |           |
| IUPAC Name                               | aluminum; lithium; hydride   |           |
| Beilstein/Reaxys<br>No.                  | N/A                          |           |
| SMILES                                   | [Li+].[AlH4-]                |           |
| Inchl Identifier                         | InChI=1S/AI.Li.4H/q-1;+1;;;; |           |
| Inchl Key                                | OCZDCIYGECBNKL-UHFFFAOYSA-N  |           |

| Signal Word              | Danger               |
|--------------------------|----------------------|
| <b>Hazard Statements</b> | H225-H260-H314-H335  |
| Hazard Codes             | F,C                  |
| Risk Codes               | 11-15-19-34-37       |
| Safety Statements        | 16-26-36/37/39-43-45 |
| RTECS Number             | N/A                  |
| Transport Information    | UN 3399 4.3/PG 1     |
| WGK Germany              | 1                    |

Create Printable PDF

### **SAFETY DATA SHEET**

**Date Accessed:** 04/25/2024 **Date Revised:** 01/15/2022

### **SECTION 1. IDENTIFICATION**

**Product Identifiers:** All applicable American Elements product codes for CAS #16853-85-3

Relevant identified uses of the substance:

Scientific research and development

Supplier details: American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551

Fax: +1 310-208-0351

Emergency telephone number: Domestic, North America +1 800-424-9300 International +1 703-527-3887

#### **SECTION 2. HAZARDS IDENTIFICATION**

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS) GHS02 Flame

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously. GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.

Hazards not otherwise classified

No data available

GHS label elements

GHS label elements, including precautionary

statements Hazard pictograms



GHS02 GHS05

Signal word

Danger

Hazard statements

H260 In contact with water releases flammable gases which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P231+P232

Handle under inert gas. Protect from moisture.

P262

Do not get in eyes, on skin, or on clothing. P280

Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair):

Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308

IF exposed or concerned:

P310

Immediately call a POISON CENTER/doctor.

P378

Use for extinction: Limestone powder.

WHMIS classification

B6 - Reactive flammable material

D2B - Toxic material causing other toxic effects

E - Corrosive material

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

Health (acute effects) = 3

Flammability = 3

Physical Hazard = 3

Other hazards

Results of PBT and vPvB assessment

PBT:

N/A

vPvB:

N/A

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

CAS No. / Substance Name:

16853-85-3 Lithium aluminum hydride

Identification number(s):

EC number:

240-877-9

Index number:

001-002-00-4

#### **SECTION 4. FIRST AID MEASURES**

Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

If inhaled:

Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

In case of skin contact:

Immediately wash with soap and water; rinse thoroughly.

Seek immediate medical advice.

In case of eye contact:

Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed:

Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed

Causes severe skin burns.

Causes serious eye damage.

Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5. FIREFIGHTING MEASURES**

Extinguishing media

Suitable extinguishing agents

Limestone powder

For safety reasons unsuitable extinguishing agents

Carbon dioxide

Foam

Water

Special hazards arising from the substance or mixture If this product is involved in a fire, the following can be released:

Lithium oxide

Aluminum oxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow product to enter drains, sewage systems, or other water courses.

Methods and materials for containment and cleanup:

Use neutralizing agent.

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Prevention of secondary hazards:

Keep away from ignition sources.

Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7. HANDLING AND STORAGE**

Handling

Precautions for safe handling

Handle under dry protective gas.

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

No data available

Conditions for safe storage, including any

incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store away from air.

Store away from water/moisture.

Store away from strong bases.

Store away from oxidizing agents.

Store away from reducing agents.

Store away from halogens.

Store away from halocarbons.

Store away from alcohols.

Further information about storage conditions:

Store under dry inert gas.

This product is moisture sensitive.

This product is air sensitive.

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Protect from humidity and water.

Specific end use(s)

No data available

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring

at the workplace:

16853-85-3 Lithium aluminum hydride (100.0%)

REL (USA) Long-term value: 2 mg/m<sup>3</sup>

as Al

TLV (USA) Long-term value: 1\* mg/m<sup>3</sup>

as AI;\*as respirable fraction

Additional information:

No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:

Use a respirator with type P100 (USA) or P3 (EN 143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if airpurifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.

Protection of hands:

Impervious gloves

Inspect gloves prior to use.

Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material (in minutes)

480

Glove thickness

0.11 mm

Eye protection:

Tightly sealed goggles

Full face protection

Body protection:

Protective work clothing.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties Appearance:

Form: Powder or pellets Color: White to grey Odor: Odorless

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: >125 °C (>257 °F) (dec)

Boiling point/Boiling range: No data available Sublimation temperature / start: No data available

Flammability (solid, gas)

Contact with water liberates extremely flammable

gases.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion: No data available.

**Explosion limits:** 

Lower: No data available Upper: No data available Vapor pressure: N/A

Density at 20 °C (68 °F): 0.917 g/cm3 (7.652 lbs/gal)

Relative density No data available. Vapor density

N/A

Evaporation rate

N/A

Solubility in Water (H<sub>2</sub>O): Reacts

Contact with water releases flammable gases Partition coefficient (n-octanol/water): No data

available.
Viscosity:
Dynamic: N/A
Kinematic: N/A
Other information
No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

In contact with water releases flammable gases which may ignite spontaneously.

Chemical stability

Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

Reacts with strong oxidizing agents

Contact with water releases flammable gases

Conditions to avoid

No data available

Incompatible materials:

Air

Bases

Oxidizing agents

Halogens

Halocarbons

**Alcohols** 

Reducing agents

Water/moisture

Hazardous decomposition products:

Lithium oxide

Aluminum oxide

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.

LD/LC50 values that are relevant for classification:

Oral LD50 85 mg/kg (mouse)

Skin irritation or corrosion:

Causes severe skin burns.

Eye irritation or corrosion:

Causes serious eye damage.

Sensitization:

No sensitizing effects known.

Germ cell mutagenicity:

No effects known.

Carcinogenicity:

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP,

OSHA or ACGIH.

Reproductive toxicity:

No effects known.

Specific target organ system toxicity - repeated exposure:

No effects known.

Specific target organ system toxicity - single exposure:

No effects known.

Aspiration hazard:

No effects known.

Subacute to chronic toxicity:

No effects known.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

Carcinogenic categories

OSHA-Ca (Occupational Safety & Health

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity** 

Aquatic toxicity:

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Additional ecological information:

Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT:

N/A

vPvB:

N/A

Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation

Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

### **SECTION 14. TRANSPORT INFORMATION**

**UN-Number** 

DOT, IMDG, IATA

UN1410

UN proper shipping name

DOT

Lithium aluminum hydride

IMDG, IATA

LITHIUM ALUMINIUM HYDRIDE

Transport hazard class(es)

DOT

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3

Class

4.3 (W2) Substances which, in contact with water, emit flammable gases

Label

4.3

IMDG, IATA

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3

Packing group

DOT, IMDG, IATA

Environmental hazards:

N/A

Special precautions for user

Warning: Substances which, in contact with water,

emit flammable gases EMS Number: F-G,S-M

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

N/A

Transport/Additional information:

DOT

Marine Pollutant (DOT):

No

UN "Model Regulation":

UN1410, Lithium aluminum hydride, 4.3, I

### SECTION 15. REGULATORY INFORMATION

Safety, health and environmental

regulations/legislation specific for the substance or mixture

GHS GHS label elements, including precautionary statements

Hazard pictograms

GHS02 GHS05

Signal word

Danger

Hazard statements

H260 In contact with water releases flammable gases which may ignite spontaneously.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P231+P232

Handle under inert gas. Protect from moisture.

P262

Do not get in eyes, on skin, or on clothing.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair):

Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308

IF exposed or concerned:

P310

Immediately call a POISON CENTER/doctor.

P378

Use for extinction: Limestone powder.

National regulations

All components of this product are listed in the U.S.

**Environmental Protection Agency Toxic Substances** 

Control Act Chemical substance Inventory.

All components of this product are listed on the

Canadian Non-Domestic Substances List (NDSL).

SARA Section 313 (specific toxic chemical listings)

Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer

Substance is not listed.

Prop 65 - Developmental toxicity

Substance is not listed.

Prop 65 - Developmental toxicity, female

Substance is not listed.

Prop 65 - Developmental toxicity, male

Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.

Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring

Authorisation for use)

Substance is not listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### 16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.