



Titanium Aluminum Carbide		Pricing >
Titanium Aluminum Carbide Sputtering Target		Pricing >
Linear Formula	Ti ₃ AlC ₂	
Pubchem CID	72374518	
MDL Number	N/A	
EC No.	N/A	
IUPAC Name	methanidyldynealumane; methanidyldynetitanium; titanium; titanium(2+)	
SMILES	[C-]#[Al].[C-]#[Ti].[Ti].[Ti+2]	
Inchl Identifier	InChI=1S/2C.Al.3Ti/q2*-1;;;+2	
Inchl Key	IVOHOIQJUAHTFQ-UHFFFAOYSA-N	
Signal Word	Danger	
Hazard Statements	H228-H261-H315-H319-H335	
Hazard Codes	Xi, F	
Precautionary Statements	P210-P231+P232-P261-P305+P351+P338-P405-P501	
Risk Codes	N/A	
Safety Statements	N/A	
Transport Information	UN1394 4.3/ PG II	
GHS Pictograms	GHS02 Flame  GHS07 Exclamation Point 	

[Create Printable PDF](#)

SAFETY DATA SHEET

Date Accessed: 04/19/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifiers: All applicable American Elements product codes for CAS #196506-01-1

Relevant identified uses of the substance:
Scientific research and development

Supplier details:
American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351

Emergency telephone number:
Domestic, North America +1 800-424-9300
International +1 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)
GHS02 Flame
Flam. Sol. 1 H228 Flammable solid.
Water-react. 2 H261 In contact with water releases flammable gas.
GHS07
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.
Hazards not otherwise classified
No data available
GHS label elements
GHS label elements, including precautionary statements
Hazard pictograms



GHS02
GHS07
Signal word
Danger
Hazard statements
H228 Flammable solid.
H261 In contact with water releases flammable gas.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
Precautionary statements
P210 Keep away from heat/sparks/open flames/hot

surfaces. No smoking.
P231+P232 Handle under inert gas. Protect from moisture.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS classification
B6 - Reactive flammable material
D2B - Toxic material causing other toxic effects
Classification system
HMIS ratings (scale 0-4)
(Hazardous Materials Identification System)
Health (acute effects) = 1
Flammability = 3
Physical Hazard = 2
Other hazards
Results of PBT and vPvB assessment
PBT: N/A
vPvB: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances
CAS No. / Substance Name: 196506-01-1
Titanium aluminum carbide

SECTION 4. FIRST AID MEASURES

Description of first aid measures
If inhaled:
Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
In case of skin contact:
Immediately wash with soap and water; rinse thoroughly.
Seek immediate medical advice.
In case of eye contact:
Rinse opened eye for several minutes under running water. Consult a physician.
If swallowed:
Seek medical treatment.
Information for doctor
Most important symptoms and effects, both acute and delayed

No data available
Indication of any immediate medical attention and special treatment needed
No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media
Suitable extinguishing agents
In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
For safety reasons unsuitable extinguishing agents
Water
Special hazards arising from the substance or mixture
If this product is involved in a fire, the following can be released:
Carbon monoxide and carbon dioxide
Metal oxide fume
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures
Use personal protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions:
Do not allow material to be released to the environment without official permits.
Methods and materials for containment and cleanup:
Keep away from ignition sources.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Prevention of secondary hazards:
Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling
Handle under dry protective gas.
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires:
Protect against electrostatic charges.
Conditions for safe storage, including any incompatibilities
Requirements to be met by storerooms and receptacles:
Store in a cool location.
Information about storage in one common storage facility:
Store away from oxidizing agents.
Store away from water/moisture.
Further information about storage conditions:
Store under dry inert gas.
This product is moisture sensitive.
Keep container tightly sealed.
Store in cool, dry conditions in well-sealed containers.
Protect from humidity and water.
Specific end use(s)
No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.
Control parameters
Components with limit values that require monitoring at the workplace:
1299-86-1 Aluminum carbide (100.0%)
PEL (USA) Long-term value: 15*; 15** mg/m³ *Total dust; ** Respirable fraction
REL (USA) Long-term value: 10* 5** mg/m³ *Total dust **Respirable fraction
TLV (USA) Long-term value: 1* mg/m³ as Al; *as respirable fraction
Additional information:
No data
Exposure controls
Personal protective equipment
Follow typical protective and hygienic practices for handling chemicals.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing

immediately.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Maintain an ergonomically appropriate working environment.
Breathing equipment:
Use suitable respirator when high concentrations are present.
Protection of hands:
Impervious gloves
Inspect gloves prior to use.
Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.
Penetration time of glove material (in minutes)
No data available
Eye protection:
Safety glasses
Full face protection
Body protection:
Protective work clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties
Appearance:
Form: Solid
Color: Dark grey
Odor: No data available
Odor threshold: No data available.
pH: N/A
Melting point/Melting range: 2100 °C (3812 °F)
Boiling point/Boiling range: No data available
Sublimation temperature / start: No data available
Flammability (solid, gas): Highly flammable. Contact with water liberates extremely flammable gases.
Ignition temperature: No data available
Decomposition temperature: >2200 °C (>3992 °F)
Autoignition: No data available.
Danger of explosion: No data available.
Explosion limits:
Lower: No data available
Upper: No data available
Vapor pressure: N/A
Density at 20 °C (68 °F): 2.36 g/cm³ (19.694 lbs/gal)
Relative density: No data available.
Vapor density: N/A
Evaporation rate: N/A
Solubility in Water (H₂O): Contact with water releases flammable gases
Partition coefficient (n-octanol/water): No data available.

Viscosity:
Dynamic: N/A
Kinematic: N/A
Other information: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

In contact with water releases flammable gases which may ignite spontaneously.

Chemical stability

Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

Contact with water releases flammable gases

Conditions to avoid

No data available

Incompatible materials:

Oxidizing agents

Water/moisture

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Metal oxide fume

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

No effects known.

LD/LC50 values that are relevant for classification:

No data

Skin irritation or corrosion:

Causes skin irritation.

Eye irritation or corrosion:

Causes serious eye irritation.

Sensitization:

No sensitizing effects known.

Germ cell mutagenicity:

No effects known.

Carcinogenicity:

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity:

No effects known.

Specific target organ system toxicity - repeated exposure:

No effects known.

Specific target organ system toxicity - single exposure:
May cause respiratory irritation.
Aspiration hazard:
No effects known.
Subacute to chronic toxicity:
Aluminum may be implicated in Alzheimers disease.
Inhalation of aluminum containing dusts may cause pulmonary disease.
Subacute to chronic toxicity:
No effects known.
Additional toxicological information:
To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity
Aquatic toxicity:
No data available
Persistence and degradability
No data available
Bioaccumulative potential
No data available
Mobility in soil
No data available
Additional ecological information:
Do not allow material to be released to the environment without official permits.
Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.
Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT:
N/A
vPvB:
N/A
Other adverse effects
No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods
Recommendation
Consult official regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation:
Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number

DOT, IMDG, IATA

UN1394

UN proper shipping name

DOT

Aluminum carbide

IMDG, IATA

ALUMINIUM CARBIDE

Transport hazard class(es)

DOT

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3

Class

4.3 (W2) Substances which, in contact with water, emit flammable gases

Label

4.3

IMDG, IATA

Class

4.3 Substances which, in contact with water, emit flammable gases.

Label

4.3

Packing group

DOT, IMDG, IATA

II

Environmental hazards:

N/A

Special precautions for user

Warning: Substances which, in contact with water, emit flammable gases

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N/A

Transport/Additional information:

DOT

Marine Pollutant (DOT):

No

UN "Model Regulation":

UN1394, Aluminum carbide, 4.3, II

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or

mixture

GHS GHS label elements, including precautionary statements

Hazard pictograms

GHS02

GHS07

Signal word

Danger

Hazard statements

H228 Flammable solid.

H261 In contact with water releases flammable gas.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P231+P232 Handle under inert gas. Protect from moisture.

P261 Avoid breathing

dust/fume/gas/mist/vapors/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.

Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.
Annex XIV of the REACH Regulations (requiring
Authorisation for use)
Substance is not listed.
Chemical safety assessment:
A Chemical Safety Assessment has not been carried
out.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.

Research

- Effect of electron irradiation on different crystal planes of titanium aluminum carbide. Xiaochen Huang, Yi Feng, Gang Qian, Yang Wang, Xuebin Zhang. *Ceramics International*, Volume 42, Issue 13, October 2016, Pages 14984-14991.
- Microstructure and mechanical properties of titanium aluminum carbides neutron irradiated at 400–700°C. Caen Ang, Chad M. Parish, Chunghao Shih, Chinthaka Silva, Yutai Katoh. *Journal of the European Ceramic Society*, Volume 37, Issue 6, June 2017, Pages 2353-2363.
- Pressureless sintering and mechanical properties of titanium aluminum carbide. Hashimoto S, Takeuchi M, Inoue K, Honda S, Awaji H, Fukuda K, Zhang S. *Materials Letters*. 2008 Apr 15;62(10-11):1480-3.
- Microstructures and adhesion of the oxide scale formed on titanium aluminum carbide substrates. Lin Z, Zhuo M, Zhou Y, Li M, Wang J. *Journal of the American Ceramic Society*. 2006 Sep;89(9):2964-6.
- Hydrothermal oxidation behavior of bulk titanium aluminum carbide. Zhang H, Presser V, Nickel KG, Berthold C, Zhou Y. *Journal of the American Ceramic Society*. 2011 Oct;94(10):3460-6.
- High-Speed Friction Characteristics and Frictional Oxidation of

Titanium Aluminum Carbide. Zhou W, Zhai H, Huang Z, Guan M. Journal-Chinese Ceramic Society. 2006;34(5):523.

- Exfoliation of Titanium Aluminum Carbide (211 MAX Phase) to Form Nanofibers and Two-Dimensional Nanosheets and Their Application in Aqueous-Phase Cadmium Sequestration. Shahzad A, Nawaz M, Moztahida M, Tahir K, Kim J, Lim Y, Kim B, Jang J, Lee DS. ACS Appl Mater Interfaces. 2019 May 29;11(21):19156-19166.
- Deep reactive ion etching of alumina titanium carbide using chlorine-based plasma. C. Pakpum, N. Pussadee. Surface and Coatings Technology, Volume 306, Part A, 25 November 2016, Pages 194-199.
- Phase segregation of titanium-aluminium carbide (Ti₂AlC) at high pressure and high temperature. Jiaqian Qin, Duanwei He, Chao Chen, Jianghua Wang, Binwei Yang. Journal of Alloys and Compounds, Volume 462, Issues 1–2, 25 August 2008, Pages 124-127.