




Copper(II) Neodecanoate		Pricing >
Linear Formula	Cu(OOC ₁₀ H ₁₉) ₂	
Pubchem CID	163179	
MDL Number	MFCD00070437	
EC No.	268-439-2	
IUPAC Name	copper; 7,7-dimethyloctanoate	
SMILES	CC(C)(C)CCCCC(=O)[O-].CC(C)(C)CCCCC(=O)[O-].[Cu+2]	
Inchl Identifier	InChI=1S/2C10H20O2.Cu/c2*1-10(2,3)8-6-4-5-7-9(11)12;/h2*4-8H2,1-3H3,(H,11,12)/q;;+2/p-2	
Inchl Key	CLUOTFHJTGLPSG-UHFFFAOYSA-	
Signal Word	Danger	
Hazard Statements	H225-H361-H373-H304-H315-H336	
Hazard Codes	F, T, Xi	
Risk Codes	N/A	
Safety Statements	N/A	
Transport Information	UN1993 3/PG III	
GHS Pictograms	GHS02 Flame  GHS08 Health Hazard  GHS07 Exclamation Point 	

[Create Printable PDF](#)

SAFETY DATA SHEET

Date Accessed: 05/18/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifiers: All applicable American Elements product codes for CAS #50315-14-5

Relevant identified uses of the substance:
Scientific research and development

Supplier details:
American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551
Fax: +1 310-208-0351

Emergency telephone number:
Domestic, North America +1 800-424-9300
International +1 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture
GHS02 Flame
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
GHS08 Health hazard
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
GHS07
Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).



Hazard pictograms
GHS02d GHS07d GHS08

Signal word Danger

Hazard-determining components of labeling:
toluene

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through

prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Classification system:
NFPA ratings (scale 0 - 4)
2
3
0
Health = 2
Fire = 3
Reactivity = 0
HMIS-ratings (scale 0 - 4)
HEALTH
FIRE
REACTIVITY
*2
3
0
Health = *2
Fire = 3
Reactivity = 0
Other hazards
Results of PBT and vPvB assessment
PBT: N/A
vPvB: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures
Description: Mixture of the substances listed below with nonhazardous additions.
Dangerous components:
108-88-3 toluene

SECTION 4. FIRST AID MEASURES

Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours

after the accident.

If inhaled: In case of unconsciousness place patient stably in side position for transportation.

In case of skin contact: Immediately wash with soap and water; rinse thoroughly.

In case of eye contact: Rinse opened eye for several minutes under running water. Consult a physician.

If swallowed: If symptoms persist consult doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed:

No data available

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

Special hazards arising from the substance or mixture

No data available

Advice for firefighters

Protective equipment: No special measures required.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to enter drains, sewage systems, or other water courses.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water courses, or sewage systems.

Methods and materials for containment and cleanup:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling:
Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
Conditions for safe storage, including any incompatibilities:
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Not required.
Further information about storage conditions:
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Specific end use(s) No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems: No further data; see item 7.
Control parameters
Components with limit values that require monitoring at the workplace:
108-88-3 toluene
PEL Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L

Medium: urine

Time: end of shift

Parameter: Toluene

0.3 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use

respiratory protective device that is independent of circulating air.

Protection of hands:

SProtective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and

varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance

of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.
Penetration time of glove material
The exact break through time has to be found out by
the manufacturer of the protective gloves and has to
be
observed.
Eye protection:
RTightly sealed goggles

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Liquid

Color: Dark green

Odor: Unpleasant

Odor threshold: Not determined.

pH: Not determined.

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 110 °C (230 °F)

Flash point: 4 °C (39 °F) (solvent)

Flammability (solid, gas): N/A

Ignition temperature: 535 °C (995 °F)

Decomposition temperature: Not determined.

Autoignition: Product is not selfigniting.

Danger of explosion: Product is not explosive.

However, formation of explosive air/vapor
mixtures are possible.

Explosion limits:

Lower: 1.2 Vol %

Upper: 7.0 Vol %

Vapor pressure at 20 °C (68 °F): 29 hPa (22 mm Hg)

Density: Not determined.

Relative density Not determined.

Vapor density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

Solvent content:

Organic solvents: 40.0 %

VOC content: 40.0 %

400.0 g/l / 3.34 lb/gl

Other information No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity No data available
Chemical stability
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
Possibility of hazardous reactions No dangerous reactions known.
Conditions to avoid No data available
Incompatible materials: No data available
Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
108-88-3 toluene
Oral LD50 5000 mg/kg (rat)
Dermal LD50 12124 mg/kg (rabbit)
Inhalative LC50/4 h 5320 mg/l (mouse)
Primary irritant effect:
on the skin: Irritant to skin and mucous membranes.
on the eye: No irritating effect.
Sensitization: No sensitizing effects known.
Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Carcinogenic categories
IARC (International Agency for Research on Cancer)
108-88-3 toluene 3
NTP (National Toxicology Program)
None of the ingredients is listed.
OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity
Aquatic toxicity: No data available
Persistence and degradability No data available
Behavior in environmental systems:
Bioaccumulative potential No data available
Mobility in soil No data available
Additional ecological information: Not known to be hazardous to water.
Results of PBT and vPvB assessment
PBT: N/A

vPvB: N/A

Other adverse effects No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to enter drains, sewage systems, or other water courses system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number

DOT, IMDG, IATA UN1993

UN proper shipping name

DOT Flammable liquids, n.o.s.

IMDG FLAMMABLE LIQUID, N.O.S.

IATA Flammable liquid, n.o.s.

Transport hazard class(es)

DOT

Class 3 Flammable liquids

Label 3

IMDG, IATA

Class 3 Flammable liquids

Label 3

Packing group

DOT, IMDG, IATA III

Environmental hazards:

Marine pollutant: No

Special precautions for user Warning: Flammable liquids

EMS Number: F-E,S-E

Stowage Category A

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code N/A

Transport/Additional information:

DOT

Quantity limitations On passenger aircraft/rail: 60L

On cargo aircraft only: 220L

IMDG

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1993 FLAMMABLE

LIQUIDS, N.O.S., 3, III

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

All ingredients are listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

All ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

All ingredients are listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

108-88-3 toluene II

TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

d~?GHS02d~?GHS07d~?GHS08

Signal word Danger

Hazard-determining components of labeling: toluene

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P280 Wear protective gloves/protective clothing/eye

protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.