

[Germanium Arsenide Selenide](#)

[Pricing >](#)

Linear Formula	Ge-As-Se
MDL Number	N/A
EC No.	N/A
SMILES	[Ge](#[As])=[Se]
Inchl Identifier	1S/AsGeSe/c1-2-3
Inchl Key	ONMAJGDZIVCQKO-UHFFFAOYSA-N
Signal Word	Danger
Hazard Statements	H301+H331-H319
Hazard Codes	N/A
Precautionary Statements	P261-P301+P310-P304+P340-P311-P321-P405-P403+P233-P501
Risk Codes	N/A
Safety Statements	N/A
Transport Information	UN1557 6.1/PG II
GHS Pictograms	GHS06 Skull and Crossbones 

[Create Printable PDF](#)

SAFETY DATA SHEET

Date Accessed: 04/20/2024

Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifiers: All applicable American Elements product codes for CAS #57673-50-4

Relevant identified uses of the substance:
Scientific research and development

Supplier details:
American Elements
10884 Weyburn Ave.
Los Angeles, CA 90024
Tel: +1 310-208-0551

Fax: +1 310-208-0351

Emergency telephone number:
Domestic, North America +1 800-424-9300
International +1 703-527-3887

SECTION 2. HAZARDS IDENTIFICATION

HMIS

Health Ratings (0-4):

Health: 3

Flammability: 1

Physical: 1



Signal Word: Danger

Hazard Statements:

H301+H331: Toxic if swallowed or if inhaled

H319 Causes serious eye irritation

Precautionary Statements:

P261 Avoid breathing dust/fume/vapor

P301+P310: IF SWALLOWED: Immediately call a
POISON CENTER or doctor/physician

P304+P340: IF INHALED: Remove victim to fresh air
and keep at rest in a position comfortable for
breathing

P311: Call a POISON CENTER or doctor/physician

P321: Specific treatment

P405: Store locked up

P403+P233: Store in a well ventilated place. Keep
container tightly closed

P501: Dispose of contents/container in accordance
with

local/regional/national/international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Family: Ceramic

Additional Names: None

Arsenic Germanium Selenide

Percentage: 100 wt%

SECTION 4. FIRST AID MEASURES

General Treatment:

Seek medical attention if symptoms persist.

Special Treatment:

None

Important Symptoms:

None

Inhalation:

Remove victim to fresh air. Supply oxygen if breathing is difficult.

Remove breathing apparatus only after contaminated clothing has been completely removed.

Ingestion:

Do not induce vomiting. Seek immediate medical attention.

Skin:

Wash affected area with mild soap and water.

Remove any contaminated clothing.

Eyes:

Flush eyes with water, blinking often for several minutes.

Remove contact lenses if present and easy to do.

Continue rinsing

SECTION 5. FIREFIGHTING MEASURES

Flammability:

Non-flammable

Extinguishing Media:

Do not use water for metal fires –use extinguishing powder.

Spec. Fire Fighting Procedure:

Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes.

See section 10 for decomposition products.

SECTION 6. ACCIDENTAL RELEASE MEASURES

If Material Is Released/Spilled:

Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation.

Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal.

Take care not to raise dust.

Environmental Precautions:

Isolate runoff to prevent environmental pollution.

SECTION 7. HANDLING AND STORAGE

Handling Conditions:

Handle under dry protective gas.

Wash thoroughly after handling.

Storage Conditions:

Store in a cool dry place in a tightly sealed container.

Store under dry inert gas.

Store apart from materials and conditions listed in section 10.

Work/Hygienic

Maintenance:

Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.

Ventilation:

Provide sufficient ventilation to maintain concentration at or below threshold limit.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Permissible Exposure Limits:

0.01 mg/m³ as As, inorganic compounds, long-term value

Threshold Limit Value:

0.01 mg/m³ as As, long-term value

Special Equipment:

None

Respiratory Protection:

Use a respirator with type P100 (USA) or P3 (EN143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.

Protective Gloves:

Nitrile rubber, NBR 0.11mm thick.

Penetration time of glove material:

480 minutes

Eye Protection:

Safety glasses or goggles

Body Protection:

Protective work clothing. Wear close-toed shoes and long sleeves/pants.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Color

Greyish

Form:
Powder, Granules, Pellets, Sputtering target, Custom parts
Odor:
Odorless
Water Solubility:
Insoluble
Boiling Point:
N/A
Melting Point:
N/A
Flash Point:
N/A
Autoignition Temperature:
N/A
Density:
N/A

SECTION 10. STABILITY AND REACTIVITY

Stability:
Stable under recommended storage conditions
Reacts With:
Acids, Halogens, Oxidizing agents
Incompatible Conditions:
Air
Hazardous Decomposition Products:
Metal oxide fume

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects:
Eyes:
May cause irritation
Skin:
May cause irritation
Ingestion:
Toxic
Inhalation:
Toxic
Chronic:
N/A
Signs & Symptoms:
N/A
Aggravated Medical Conditions:
N/A
Median Lethal Dose:
145 mg/kg for mouse by mouth as As
769 mg/kg for rat by mouth as As
Carcinogen:

Arsenic:

EPA-A: human carcinogen: sufficient evidence from epidemiologic

studies to support a causal association between exposure and cancer

IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.

ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.

Carcinogen as defined by OSHA.

NTP-K: Known to be carcinogenic: sufficient evidence from human studies.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

High

Persistent Bioaccumulation Toxicity:

No

Very Persistent, Very Bioaccumulative:

No

Notes:

Very toxic for aquatic organism.

May cause long lasting harmful effect on aquatic life.

Do not allow material to be released to the environment without official permits.

Do not allow product to reach any water sources.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.

Avoid transfer into the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, national, and international regulations.

SECTION 14. TRANSPORT INFORMATION

Hazardous:

Hazardous for transportation.

Hazard Class:

6.1 Toxic substances.

Packing Group: II

UN Number: UN1557
Proper Shipping Name: Arsenic compounds, solid,
inorganic, n.o.s.(Germanium arsenic selenide)

SECTION 15. REGULATORY INFORMATION

Sec 302 Extremely Hazardous:

No

Sec 304 Reportable Quantities:

N/A

Sec 313 Toxic Chemicals:

Components: Arsenic

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.
