



<a href="#">Potassium Selenate</a>		<a href="#">Pricing &gt;</a>
Linear Formula	$K_2SeO_4$	
Pubchem CID	62680	
MDL Number	N/A	
EC No.	232-214-7	
IUPAC Name	potassium selenate	
Beilstein/Reaxys No.	N/A	
SMILES	[K+].[K+].[O-][Se]([O-])(=O)=O	
InchI Identifier	InChI=1S/2K.H2O4Se/c;;1-5(2,3)4/h;;(H2,1,2,3,4)/q2+1;/p-2	
InchI Key	YAZJAPBTUDGMKO-UHFFFAOYSA-L	
Signal Word	N/A	
Hazard Statements	N/A	
Hazard Codes	N/A	
Risk Codes	N/A	
Safety Statements	N/A	
Transport Information	N/A	
GHS Pictograms	<a href="#">GHS08 Health Hazard</a>  <a href="#">GHS06 Skull and Crossbones</a> 	

[Create Printable PDF](#)

## SAFETY DATA SHEET

Date Accessed: 05/03/2024

Date Revised: 01/15/2022

### SECTION 1. IDENTIFICATION

**Product Identifiers:** All applicable American Elements product codes for CAS #7790-59-2

**Relevant identified uses of the substance:**

Scientific research and development

**Supplier details:**

American Elements  
10884 Weyburn Ave.  
Los Angeles, CA 90024  
Tel: +1 310-208-0551  
Fax: +1 310-208-0351

**Emergency telephone number:**

Domestic, North America +1 800-424-9300  
International +1 703-527-3887

---

**SECTION 2. HAZARDS IDENTIFICATION**

Classification of the substance or mixture in  
accordance with 29 CFR 1910 (OSHA HCS)

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H331 Toxic if inhaled.

GHS08 Health hazard

STOT RE 2 H373 May cause damage to the central  
nervous system, the liver and the digestive system  
through prolonged or repeated exposure. Route of  
exposure: Oral, Inhalative.

Hazards not otherwise classified

No data available

GHS label elements

GHS label elements, including precautionary  
statements

Hazard pictograms



GHS06 GHS08

Signal word: Danger

Hazard statements

H301+H331 Toxic if swallowed or if inhaled.

H373 May cause damage to the central nervous  
system, the liver and the digestive system through  
prolonged or repeated exposure.

Route of exposure: Oral, Inhalative.

Precautionary statements

P260 Do not breathe  
dust/fume/gas/mist/vapors/spray.

P261 Avoid breathing  
dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a  
POISON CENTER/ doctor/...

P304+P340 IF INHALED: Remove person to fresh air  
and keep comfortable for breathing.

P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.  
WHMIS classification  
D1A - Very toxic material causing immediate and serious toxic effects  
Classification system  
HMIS ratings (scale 0-4)  
(Hazardous Materials Identification System)  
HEALTH  
FIRE  
REACTIVITY  
2  
0  
1  
Health (acute effects) = 2  
Flammability = 0  
Physical Hazard = 1  
Other hazards  
Results of PBT and vPvB assessment  
PBT: N/A  
vPvB: N/A

---

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances  
CAS No. / Substance Name:  
7790-59-2 Potassium selenate  
Identification number(s):  
EC number: 232-214-7  
Index number: 034-002-00-8

---

### **SECTION 4. FIRST AID MEASURES**

Description of first aid measures  
General information  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing has been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.  
If inhaled:  
Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm.  
Seek immediate medical advice.  
In case of skin contact:  
Immediately wash with soap and water; rinse thoroughly.  
Seek immediate medical advice.

In case of eye contact:  
Rinse opened eye for several minutes under running water. Consult a physician.  
If swallowed:  
Do not induce vomiting; immediately call for medical help.  
Information for doctor  
Most important symptoms and effects, both acute and delayed  
No data available  
Indication of any immediate medical attention and special treatment needed  
No data available

---

## **SECTION 5. FIREFIGHTING MEASURES**

Extinguishing media  
Suitable extinguishing agents  
Product is not flammable. Use fire-fighting measures that suit the surrounding fire.  
Special hazards arising from the substance or mixture  
If this product is involved in a fire, the following can be released:  
Toxic metal oxide fume  
Advice for firefighters  
Protective equipment:  
Wear self-contained respirator.  
Wear fully protective impervious suit.

---

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures  
Use personal protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Environmental precautions:  
Do not allow material to be released to the environment without official permits.  
Methods and materials for containment and cleanup:  
Dispose of contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Prevention of secondary hazards:  
No special measures required.  
Reference to other sections  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

---

## **SECTION 7. HANDLING AND STORAGE**

### Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

The product is not flammable

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Specific end use(s)

No data available

---

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Selenium and selenium compounds (as Se)  
mg/m<sup>3</sup>

ACGIH TLV 0.2

Austria MAK 0.1

Belgium TWA 0.2

Denmark TWA 0.1

Finland TWA 0.1; 0.3-STEL

Germany MAK 0.1

Hungary 0.1-STEL

Japan OEL 0.1

Korea TLV 0.2

Netherlands MAC-TGG 0.2

Poland TWA 0.1; 0.3-STEL

Sweden NGV 0.1

Switzerland MAK-W 0.1

United Kingdom TWA 0.1

USA PEL 0.2

7790-59-2 Potassium selenate (100.0%)

PEL (USA) Long-term value: 0.2 mg/m<sup>3</sup> as Se

REL (USA) Long-term value: 0.2 mg/m<sup>3</sup> as Se

TLV (USA) Long-term value: 0.2 mg/m<sup>3</sup> as Se

Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Impervious gloves

Inspect gloves prior to use.

Suitability of gloves should be determined both by material and quality, the latter of which may vary by manufacturer.

Penetration time of glove material (in minutes): No data available

Eye protection: Safety glasses

Body protection: Protective work clothing.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Powder

Color: White

Odor: Odorless

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: No data available

Boiling point/Boiling range: No data available

Sublimation temperature / start: No data available

Flash point: N/A

Flammability (solid, gas): No data available.

Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion:

Product does not present an explosion hazard.

Explosion limits:  
Lower: No data available  
Upper: No data available  
Vapor pressure: N/A  
Density at 20 °C (68 °F): 3.066 g/cm<sup>3</sup> (25.586 lbs/gal)  
Relative density: No data available.  
Vapor density: N/A  
Evaporation rate: N/A  
Solubility in Water (H<sub>2</sub>O): Soluble  
Partition coefficient (n-octanol/water): No data available.  
Viscosity:  
Dynamic: N/A  
Kinematic: N/A  
Other information  
No data available

---

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity  
No data available  
Chemical stability  
Stable under recommended storage conditions.  
Thermal decomposition / conditions to be avoided:  
Decomposition will not occur if used and stored according to specifications.  
Possibility of hazardous reactions  
No dangerous reactions known  
Conditions to avoid  
No data available  
Incompatible materials:  
Oxidizing agents  
Hazardous decomposition products:  
Toxic metal oxide fume

---

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on toxicological effects  
Acute toxicity:  
Toxic if inhaled.  
Toxic if swallowed.  
LD/LC50 values that are relevant for classification: No data  
Skin irritation or corrosion: Irritant to skin and mucous membranes.  
Eye irritation or corrosion: Irritating effect.  
Sensitization: No sensitizing effects known.  
Germ cell mutagenicity: No effects known.  
Carcinogenicity:  
No classification data on carcinogenic properties of

this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure:

May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, Inhalative.

Specific target organ system toxicity - single exposure: No effects known.

Aspiration hazard: No effects known.

Other information (about experimental toxicology):

Reproductive effects have been observed on tests with laboratory animals.

Subacute to chronic toxicity:

Selenium may cause amyotrophic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatigue, loss of fingernails and hair, pulmonary edema, anemia and weight loss.

Subacute to chronic toxicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) reports the following effects in laboratory animals:

Related to Chronic Data - death.

Reproductive - Effects on Newborn - weaning or lactation index (e.g., # alive at weaning per # alive at day 4).

Reproductive - Fertility - female fertility index (e.g. # females pregnant per # sperm positive females; # females pregnant per # females mated)

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

---

## SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Ecotoxicological effects:

Remark:

Very toxic for aquatic organisms

Additional ecological information:

Do not allow material to be released to the

environment without official permits.  
Do not allow product to reach groundwater, water courses, or sewage systems, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
May cause long lasting harmful effects to aquatic life.  
Avoid transfer into the environment.  
Very toxic for aquatic organisms  
Results of PBT and vPvB assessment  
PBT: N/A  
vPvB: N/A  
Other adverse effects  
No data available

---

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste treatment methods  
Recommendation  
Consult official regulations to ensure proper disposal.  
Uncleaned packagings:  
Recommendation:  
Disposal must be made according to official regulations.  
Recommended cleansing agent:  
Water, if necessary with cleansing agents.

---

## **SECTION 14. TRANSPORT INFORMATION**

UN-Number  
DOT, IMDG, IATA  
UN2630  
UN proper shipping name  
DOT  
Selenates (Potassium selenate)  
IMDG, IATA  
SELENATES (Potassium selenate)  
Transport hazard class(es)  
DOT  
Class  
6.1 Toxic substances.  
Label  
6.1  
Class  
6.1 (T5) Toxic substances  
Label  
6.1  
IMDG, IATA  
Class  
6.1 Toxic substances.

Label  
6.1  
Packing group  
DOT, IMDG, IATA  
I  
Environmental hazards:  
Environmentally hazardous substance, solid  
Special precautions for user  
Warning: Toxic substances  
Transport in bulk according to Annex II of  
MARPOL73/78 and the IBC Code  
N/A  
Transport/Additional information:  
DOT  
Marine Pollutant (DOT):  
No  
UN "Model Regulation":  
UN2630, Selenates (Potassium selenate), 6.1, I

---

## **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture  
GHS GHS label elements, including precautionary statements  
Hazard pictograms:  
GHS06  
GHS08  
Signal word: Danger  
Hazard statements  
H301+H331 Toxic if swallowed or if inhaled.  
H373 May cause damage to the central nervous system, the liver and the digestive system through prolonged or repeated exposure.  
Route of exposure: Oral, Inhalative.  
Precautionary statements  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.  
National regulations  
All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL).  
SARA Section 313 (specific toxic chemical listings)  
7790-59-2 Potassium selenate  
California Proposition 65  
Prop 65 - Chemicals known to cause cancer  
Substance is not listed.  
Prop 65 - Developmental toxicity  
Substance is not listed.  
Prop 65 - Developmental toxicity, female  
Substance is not listed.  
Prop 65 - Developmental toxicity, male  
Substance is not listed.  
Information about limitation of use:  
For use only by technically qualified individuals.  
This product contains selenium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.  
Other regulations, limitations and prohibitive regulations  
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006.  
Substance is not listed.  
The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.  
Substance is not listed.  
Annex XIV of the REACH Regulations (requiring Authorisation for use)  
Substance is not listed.  
Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

---

## **16. OTHER INFORMATION**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022  
AMERICAN ELEMENTS. LICENSED GRANTED TO  
MAKE UNLIMITED PAPER COPIES FOR INTERNAL

USE ONLY.

---