

SAFETY DATA SHEET

Date Printed: 04/24/2024 Date Revised: 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: (2N) 99% Bismuth Tellurium Selenide

Product Code: BI-TESE-02-C

CAS Number: N/A

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551 Fax: +1 310-208-0351 Emergency telephone number: +1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture GHS02 Flame H228 Flammable solid. H303 May be harmful if swallowed. Classification according to Directive 67/548/EEC or Directive 1999/45/EC F; Highly flammable R11: Highly flammable. Information concerning particular hazards for human and environment: N/A Label elements Labelling according to EU guidelines: Observe the general safety regulations when handling chemicals Code letter and hazard designation of product: F Highly flammable **Risk phrases:** 11 Highly flammable. Safety phrases: 33 Take precautionary measures against static discharges. Hazard description:



WHMIS classification B4 - Flammable solid Classification system HMIS ratings (scale 0-4) (Hazardous Materials Identification System) Health (acute effects) = 1 Flammability = 2 Reactivity = 1 Other hazards Results of PBT and vPvB assessment PBT: N/A vPvB: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Bismuth 7440-69-9 Tellurium 13494-80-9 Selenium 7782-49-2

SECTION 4. FIRST AID MEASURES

Description of first aid measures If inhaled: Supply patient with fresh air. If not breathing, provide artificial respiration. Keep patient warm. Seek immediate medical advice. In case of skin contact: Immediately wash with soap and water; rinse thoroughly. Seek immediate medical advice. In case of eye contact: Rinse opened eye for several minutes under running water. Consult a physician. If swallowed: Seek medical treatment. Information for doctor Most important symptoms and effects, both acute and delayed No data available Indication of any immediate medical attention and special treatment needed No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media Suitable extinguishing agents Special powder for metal fires. Do not use water. For safety reasons unsuitable extinguishing agents Water Special hazards arising from the substance or mixture In case of fire, the following can be released: Metal oxide fume Advice for firefighters Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources Environmental precautions: Do not allow material to be released to the environment without official permits. Methods and materials for containment and cleanup: Ensure adequate ventilation. Keep away from ignition sources. Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling Keep container tightly sealed. Store in cool, dry place in tightly closed containers. Ensure good ventilation at the workplace. Information about protection against explosions and fires: Protect against electrostatic charges. Conditions for safe storage, including any incompatibilities Requirements to be met by storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Do not store together with acids. Store away from oxidizing agents. Store away from halogens. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well-sealed containers. Specific end use(s) No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals. Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present. Protection of hands:

Impervious gloves

Inspect gloves prior to use. Material of gloves The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer. Eye protection: Safety glasses Body protection: Protective work clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties General Information Appearance: Form: Powder Color: Grev Odor: Odorless Odor threshold: No data available. pH: N/A Melting point/Melting range: 271.4°C (521 °F) Boiling point/Boiling range: 1564°C (2847 °F) Sublimation temperature / start: No data available Flash point: N/A Flammability (solid, gas) Highly flammable. Ignition temperature: No data available Decomposition temperature: No data available Autoignition: No data available. **Explosion limits:** Lower: No data available Upper: No data available Vapor pressure at 840°C (1544 °F): 1 hPa (1 mm Hg) Density at 20°C (68 °F): 9.79 g/cm³ (81.698 lbs/gal) Bulk density at 20°C (68 °F): 6000 kg/m³ Relative density No data available. Vapor density N/A Evaporation rate N/A Solubility in / Miscibility with Water: Insoluble Segregation coefficient (n-octonol/water): No data available. Viscosity: Dynamic: N/A Kinematic: N/A

Other information No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications. Possibility of hazardous reactions No dangerous reactions known Incompatible materials: Acids Halogens Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects Acute toxicity: LD/LC50 values that are relevant for classification: Oral LD50 10000 mg/kg (mouse) 5000 mg/kg (rat) Primary irritant effect: on the skin: May cause irritation on the eye: May cause irritation Sensitization: No sensitizing effects known. Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known. No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH. The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute and/or other multiple dose toxicity data for components in this product.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Acquatic toxicity: No data available Persistence and degradability No data available Behavior in environmental systems: Bioaccumulative potential No data available Mobility in soil No data available Additional ecological information: Do not allow material to be released to the environment without official permits. Results of PBT and vPvB assessment PBT: N/A vPvB: N/A Other adverse effects No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods Recommendation Consult official regulations to ensure proper disposal. Uncleaned packagings: Recommendation: Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number DOT, ADR, IMDG, IATA UN3089 UN proper shipping name DOT, IMDG, IATA METAL POWDER, FLAMMABLE, N.O.S. (Bismuth) ADR 3089 METAL POWDER, FLAMMABLE, N.O.S. (Bismuth) Transport hazard class(es) DOT, IMDG, IATA Class 4.1 Flammable solids, self-reactive substances and solid desensitised explosives. Label 4.1 ADR Class 4.1 (F3) Flammable solids, self-reactive substances and solid desensitised explosives Label 4.1 Packing group DOT, ADR, IMDG, IATA III Environmental hazards: Marine pollutant: No Special precautions for user Warning: Flammable solids, self-reactive substances and solid desensitised explosives Danger code (Kemler): 40 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N/A UN "Model Regulation": UN3089, METAL POWDER, FLAMMABLE, N.O.S.(Bismuth), 4.1, III

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture Product related hazard informations: Observe the general safety regulations when handling chemicals Hazard symbols: F Highly flammable **Risk phrases:** 11 Highly flammable. Safety phrases: 33 Take precautionary measures against static discharges. National regulations All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory. All components of this product are listed on the Canadian Domestic Substances List (DSL). Information about limitation of use: For use only by technically gualified individuals. Other regulations, limitations and prohibitive regulations REACH - Pre-registered substances Substance is listed. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.

AMERICAN ELEMENTS | 10884 WEYBURN AVE. | LOS ANGELES, CALIFORNIA 90024 TEL. 310-208-0551 | FAX 310-208-0351 | customerservice@americanelements.com