

SAFETY DATA SHEET

Date Printed: 04/24/2024 **Date Revised:** 01/15/2022

SECTION 1. IDENTIFICATION

Product Identifier: (3N) 99.9% Beryllium Cubes

Product Code: BE-M-03-CB

CAS Number: 7440-41-7

Relevant identified uses of the substance: Scientific research and development

Supplier details:

American Elements 10884 Weyburn Ave. Los Angeles, CA 90024 Tel: +1 310-208-0551

Tel: +1 310-208-0551 Fax: +1 310-208-0351

Emergency telephone number:

+1 800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 2 H330 Fatal if inhaled.

GHS08 Health hazard

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung and the blood through prolonged or repeated exposure.

Route of exposure: Inhalative.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T+; Very toxic

R26: Very toxic by inhalation.

T: Toxic

R49-25-48/23: May cause cancer by inhalation. Toxic if swallowed. Toxic: danger of serious damage to health by prolonged exposure through inhalation.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

Xi; Sensitizing

R43: May cause sensitization by skin contact.

Carc. Cat. 2

Information concerning particular hazards for human and environment:

N/A

Hazards not otherwise classified

No data available

Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labeled according to the CLP regulation.

Hazard pictograms





GHS06 GHS08

Signal word: Danger

Hazard statements

H301 Toxic if swallowed.

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH

FIRE

REACTIVITY

1

0

0

Health (acute effects) = 1

Flammability = 0

Physical Hazard = 0

Other hazards

Results of PBT and vPvB assessment

PBT: N/A

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

CAS No. / Substance Name:

7440-41-7 Beryllium

Identification number(s): EC number: 231-150-7

Index number: 004-001-00-7

SECTION 4. FIRST AID MEASURES

Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing has been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

No special measures required.

If inhaled:

Seek medical treatment in case of complaints.

In case of skin contact:

Generally the product does not irritate the skin.

In case of eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

If swallowed:

Do not induce vomiting; immediately call for medical help.

Information for doctor

Most important symptoms and effects, both acute and delayed

No data available

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5. FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents

Special powder for metal fires. Do not use water.

For safety reasons unsuitable extinguishing agents

Water

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Toxic metal oxide fume

Advice for firefighters

Protective equipment:

No special measures required.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions:

Do not allow material to be released to the environment without official permits.

Do not allow product to enter drains, sewage systems, or other water courses.

Do not allow material to penetrate the ground or soil.

Methods and materials for containment and cleanup:

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Prevention of secondary hazards:

No special measures required.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

No special measures required.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from strong bases.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed containers.

Specific end use(s)

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical systems:

No further data; see section 7.

Control parameters

Components with limit values that require monitoring at the workplace:

7440-41-7 Beryllium (100.0%)

PEL (USA) Long-term value: 0.002 mg/m³

Ceiling limit value: 0.005; 0.025* mg/m³ as Be; *30 min peak per 8-hr shift

REL (USA) Ceiling limit value: 0.0005 mg/m³ as Be; See Pocket Guide App. A

TLV (USA) Long-term value: 0.00005* mg/m³ as Be;*inhalable; (SEN)NIC-DSEN;RSEN;Skin

EL (Canada) Long-term value: 0.002 mg/m³ as Be; ACIGH A1, IARC 1

EV (Canada) Short-term value: 0.01 mg/m³

Long-term value: 0.002 mg/m³ as Be Additional information: No data

Exposure controls

Personal protective equipment

Follow typical protective and hygienic practices for handling chemicals.

Store protective clothing separately. Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment:

Not required.

Use self-contained respiratory protective device in emergency situations.

Protection of hands: Not required.

Penetration time of glove material (in minutes): No data available

Eye protection: Safety glasses

Body protection: Protective work clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance:

Form: Solid in various forms

Color: Grey Odor: Odorless

Odor threshold: No data available.

pH: N/A

Melting point/Melting range: 1278 °C (2332 °F) Boiling point/Boiling range: 2471 °C (4480 °F) Sublimation temperature / start: No data available Flammability (solid, gas): No data available. Ignition temperature: No data available

Decomposition temperature: No data available

Autoignition: No data available.

Danger of explosion: No data available.

Explosion limits:

Lower: No data available Upper: No data available

Vapor pressure at 990 °C (1814 °F): 0.000133 hPa

Density at 20 °C (68 °F): 1.848 g/cm³ (15.422 lbs/gal)

Relative density: No data available.

Vapor density: N/A Evaporation rate: N/A

Solubility in Water (H₂O): Insoluble

Partition coefficient (n-octanol/water): No data available.

Viscosity: Dynamic: N/A Kinematic: N/A Other information No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions

No dangerous reactions known

Conditions to avoid

No data available

Incompatible materials:

Acids

Bases

Hazardous decomposition products:

Toxic metal oxide fume

SECTION 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

Fatal if inhaled.

Toxic if swallowed.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion:

Generally the product does not irritate the skin.

Causes skin irritation.

Eye irritation or corrosion:

Causes serious eye damage.

Sensitization:

May cause an allergic skin reaction.

Germ cell mutagenicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.

Carcinogenicity:

May cause cancer.

IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.

ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.

EPA-B1: Probable human carcinogen, limited evidence of carcinogenicity from epidemiologic studies.

NTP-K: Known to be carcinogenic: sufficient evidence from human studies.

The Registry of Toxic Effects of Chemical Substances (RTECS) contains tumorigenic and/or carcinogenic and/or neoplastic data for this substance.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure:

Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Specific target organ system toxicity - single exposure:

May cause respiratory irritation.

Aspiration hazard:

No effects known.

Subacute to chronic toxicity:

The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Additional ecological information:

Do not allow material to be released to the environment without official permits.

Do not allow undiluted product or large quantities to reach groundwater, water courses, or sewage systems.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: N/A vPvB: N/A

Other adverse effects No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation

Consult official regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation:

Disposal must be made according to official regulations.

SECTION 14. TRANSPORT INFORMATION

UN-Number

DOT, ADN, IMDG, IATA

N/A

UN proper shipping name

DOT, ADN, IMDG, IATA

N/A

Transport hazard class(es)

DOT, ADR, ADN, IMDG, IATA

Class

N/A

Packing group

DOT, IMDG, IATA

N/A

Environmental hazards:

N/A

Special precautions for user

N/A

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N/A

Transport/Additional information:

DOT

Marine Pollutant (DOT):

No

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings)

7440-41-7 Beryllium

California Proposition 65

Prop 65 - Chemicals known to cause cancer

7440-41-7 Beryllium

Prop 65 - Developmental toxicity

Substance is not listed.

Prop 65 - Developmental toxicity, female

Substance is not listed.

Prop 65 - Developmental toxicity, male

Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use)

Substance is not listed.

REACH - Pre-registered substances

Substance is listed.

Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16. OTHER INFORMATION

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH). The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. American Elements shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. COPYRIGHT 1997-2022 AMERICAN ELEMENTS. LICENSED GRANTED TO MAKE UNLIMITED PAPER COPIES FOR INTERNAL USE ONLY.